



Paving & Stone Patio Sealer

PAVING / STONE

Water based impregnating sealer for all types of natural stone and concrete paving / Exterior Use

DESCRIPTION

Water based impregnating sealer for all types of natural stone and concrete paving, honed, rough cut, flamed and brushed stone surfaces. Provides a delicately enhanced natural finish. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe. Helps reduce efflorescence.

DIRECTIONS

Preparation

Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. First wash surfaces with a dilute solution of Rocatex Tile & Stone Renovator 1: 5 and scrub with a nylon scrubbing pad or deck brush. Rinse well with water and a hose to remove any released residues and leave to dry (24hrs).

Application

Shake bottle before use. Apply evenly using foam roller, paint brush or light pressure sprayer. On more absorbent surfaces apply further coats at hourly intervals until the surface is fully saturated. On vertical surfaces always apply from the bottom up and wipe up any drips if they occur. Do not use when surfaces are very cold or very hot. Ideally between 5 - 25°C. Always test on a small area before general application to help establish best method and optimum number of coats required.

COVERAGE: M² PER COAT

| | |
|--------------------------|--------------------|
| | 5 LTR |
| Honed surfaces | 150m ² |
| Medium porosity surfaces | 75m ² |
| High porosity surfaces | 37.5m ² |

STORAGE INFORMATION

Store in a cool, dry, frost free environment.

Store locked up. Shelf Life – Up to 2 years for un-opened containers.

OTHER

Empty containers are recyclable. Active ingredients are water soluble and inert once cured. On higher porosity materials sufficient sealer should be applied until treated surfaces are fully saturated. Saturation has normally been achieved when an even layer of sealer is still visible on the surface after 20 minutes. Leave it to dry. Do not use in temperatures under 5°C or over 25°C. Clean application tools and brushes with water after use.

ROCATEX

Rocatex Ltd
Camwal Park
Camwal Road
Harrogate, HG1 4PT

T: +44 (0)1423 882 990
F: +44 (0)1423 299 040
E: info@rocatex.com
www.rocatex.com

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

HEALTH, SAFETY & ENVIRONMENTAL

Contains: 2-METHYLISOTHIAZOL-3(2H)-ONE. May cause an allergic skin reaction. Keep out of reach of children. Wear protective gloves/protective clothing/eye protection/ face protection.

IF ON SKIN: Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/ attention.



WARNING

ROCATEX

Rocatex Ltd
Camwal Park
Camwal Road
Harrogate, HG1 4PT

T: +44 (0)1423 882 990
F: +44 (0)1423 299 040
E: info@rocatex.com
www.rocatex.com

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.