



C-10 Ultimate Sealer

A high performance VOC free water-based impregnating sealer which provides an invisible, durable, protective barrier against stains, dirt, mould and limescale. Suitable for polished and unpolished natural stone, grout joints, paving, concrete and render.

- Suitable for Polished & Unpolished Natural Stone
- Also for Grout / Paving / Concrete / Brick / Render
- Excellent Stain & Dirt Protection
- Fights Against Mould & Limescale
- Easy to Apply - Only 1 to 2 Coats Required
- Invisible Finish - Does Not Alter Surface Appearance
- Highly Repellent Long Lasting Protection
- Interior / Exterior / Domestic / Commercial

DESCRIPTION

A high performance VOC free water-based impregnating sealer designed using the very latest technology in fluorochemistry. This versatile and easy to apply penetrating and invisible sealer provides a durable, non-film-forming protective barrier on porous acid sensitive surfaces including polished and unpolished natural stone, grout joints, paving, concrete and render. ROCATEX C-10 Ultimate Sealer allows the surface to breathe and provides excellent oil, grease and water repellency, stain resistance and ease of cleaning.

DIRECTIONS

Shake the bottle before use and ensure surface to be treated is completely clean, dry and free from dirt, grime and any excess cement and grout residues. If necessary, first wash the surface with a dilute solution of ROCATEX Tile & Stone Renovator 1:10. Rinse well to remove residues and leave to dry. It is important to remove any factory applied sealer or wax from the surface of porcelain before sealing.

Apply this sealer generously using a ROCATEX Sealer Applicator or sponge, brush, roller, paint pad or spray applicator and remove any excess solution after 15-30 minutes. A second application is recommended after 1 hour to ensure complete coverage and again remove any excess solution after 15-30 minutes.

Treated areas should be dry enough to walk on after about 1 hour but will take 72 hours to become fully resistant. During this time DO NOT cover the surface and wipe up any spills immediately. Consideration should also be given to any moisture trapped in a surface on newly laid floors in terms of covering the surface after sealer application.

To check that the surface has been adequately sealed a simple water bead test can be performed. This is achieved by applying a teaspoon of water onto the sealed surface and leave for 15 minutes, if bead is absorbed then another coat is required. Do not apply in direct sunlight or in temperatures exceeding 25°C. Do not allow any residues to dry on the surface and you must NOT apply if an underfloor heating system is on. Do not grout until 4 hours after applying the sealer. Tip: Without prior experience or in cases of doubt, try the product in an inconspicuous area prior to use.

COVERAGE

Higher porosity surfaces:

Per 1 litre approximately 7.5m² per coat.

Lower porosity surfaces:

Per 1 litre approximately 15m² per coat.

Polished surfaces:

Per 1 litre approximately 30m² per coat.

Grout joints:

Per 1 litre approx. 1000 linear metres per coat.

ROCATEX

Rocatex Ltd
3+4 Camwal Park
Camwal Road
Harrogate, HG1 4PT

T: +44 (0)1423 882 990
F: +44 (0)1423 299 040
E: info@rocatex.com
www.rocatex.com

This information is offered without guarantee. Our Company policy is one of continuous research and development, we therefore reserve the right to update this information at any time without prior notice. We guarantee the consistent high quality of our products, however, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof. If in doubt, conduct a small test or obtain further technical advice.

MAINTENANCE

Routinely sweep the floor and wash with ROCATEX Tile & Stone Cleaner, clean walls and work surfaces with ROCATEX Tile & Stone Cleaner.

STORAGE

Store in a cool, dry, frost-free environment between +5°C and +25°C. Shelf life can be up to 2 years in the original unopened containers.